

MBA45G INV**Teknik Bilgi/Technical Information****KARAKTERİSTİK ÖZELLİKLER / CHARACTERISTICS**

İKLİM SINIFI	CLIMATE CLASS	: N
ÇALIŞMA SICAKLIĞI	TEMPERATURE RANGE	: +2 / +8
ENERJİ TÜKETİMİ	ENERGY CONSUMP.	: 0.184 kWh/24h
ENERJİ SINIFI	ENERGY CLASS.	: A+++
GÜÇ	POWER	: 44 W
VOLTAJ/FREKANS	VOLTAGE/FREG.	: 220-240 V AC ; 50/60 Hz.
SES DÜZEYİ (dB)	Sound Pressure Level (dB)	: 26-29 dB @ 1500 rpm

AKSESUARLAR VE KONTROL LAMBALARI / ACCESSORIES AND CONTROL LAMPS

İÇ AYDINLATMA LAMBASI	INTERNAL LIGHT	: Standard
CAM KAPI	GLASS DOOR	: Optional
KAPI KİLİDİ	LOCKABLE DOOR	: Optional
SİYAH / BEYAZ RENK	BLACK AND WHITE COLOR	: Standard

TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATIONS

DIŞ BOYUTLAR	EXTERNAL DIMS. (WxDxH)	: 425x455x565
İÇ BOYUTLAR	INTERNAL DIMS. (WxDxH)	: 361x252x486
BRÜT HACİM	GROSS VOLUME	: 45 L
NET HACİM	NET VOLUME	: 41 L
BRÜT AĞIRLIK	GROSS WEIGHT	: 22 KG
NET AĞIRLIK	NET WEIGHT	: 21 KG
DIŞ GÖVDE	OUTER BODY	: PVC-coated sheet
İÇ GÖVDE	INNER LINER	: ABS / HIPS
YALITIM MADDESİ	INSULATION MATERIAL	: Sert P.U./Rigid P.U.
YALITIM MAD. YOĞUNLUĞU	INSULATION DENSITY	: 40~44 kg/m ³
KOMPR.KAPASİTESİ	COMP.CAPASITY (kcal / W)	: 52 / 44
KONDENSER	CONDENSER	: Back kondanser
KURUTUCU-FİLTRE	DRYER-FILTER	: 13,5 g 4.76x2.5mm. XH7
MEKANİK TERMOSTAT	MECHANIC THERMOSTAT	: KPF 1127 XF
SOĞUTUCU AKIŞKAN	REFRIGERANT	: R600A
SOĞ. AKIŞKAN MİKTARI	REFRIGERANT CHARGE	: 20gr
UYGUNLUK DİREKTİFİ	DIRECTIVES	: Low Voltage Directive (73/23/EEC)
STANDARTLAR	STANDARTS	: EN 60335-2-24
KOLİ ÖLÇÜSÜ	PACKAGE (WxDxH)	: 445x465x592

Teknik özellik sayfa no / Technical spec. Page no : 7 / 7**Revizyon no / Revision no : 001****Tarih/Date:16.09.2021****Hazırlayan/Prepared****Ahmet Eyüp İşler****AR-GE Müh./R&D Engineer****Revizyon tarihi / Revision date : 14.08.2018****AIKON LTD.ŞTİ.**